

Swing Hanger – Bow Shackle Type

M8

PRODUCT NAME	Stainless Steel Swing Hanger – Bow Shackle Type – M8
PRODUCT CODE	DEC-SHB-SS316
PRODUCT CATEGORY	Anchor Point Component
MATERIAL	Marine Grade SS316 Stainless Steel



PRODUCT DESCRIPTION

Heavy-duty stainless steel swing hanger with integrated bow shackle connection. Designed as an anchorage and articulation point for horizontal lifeline systems, allowing controlled movement while maintaining a secure attachment.

KEY FEATURES

- ✓ Marine Grade SS316 Stainless Steel
- ✓ Excellent Corrosion Resistance
- ✓ Adjustable Cable Tension
- ✓ Easy Installation
- ✓ Suitable for Permanent Lifeline Systems
- ✓ Low Maintenance Design

APPLICATIONS

- Horizontal Lifeline Systems
- Roof Safety Systems
- Industrial Structure
- Mining Facilities
- Telecommunications Towers
- Solar Panel Installations
- Rope Access Safety Systems

COMPLIANCE & STANDARDS

This product is manufactured and tested in accordance with international and South African standard including.

EN	EN	EN	SANS	SANS	SANS	ISO
795	353	362	50353	50795	795	9001
Personal Fall Protection Anchor Devices	Guided Type Fall Attachment	Connectors for Personal Protection Equipment	Personal Fall Protection Anchor Devices	Anchor Device	Fall Protection Anchor Devices	Quality Management Manufacturing Systems



INSTALLATION REQUIREMENTS



- Installation in accordance with applicable engineering designs and specification.
- Horizontal lifeline range is based on the sound engineer principles.
- Ensure correct wire cable fusion to anchor point.
- Use Calibrated installation tools.
- Users must be competent prefer trained personal.
- Inspect all connections before system commissioning.

INSPECTION & MAINTENANCE

INSPECTION ITEM	FREQUENCY
• Visual Inspection	Monthly
• Competent Person Inspection	Annually
• Deformation Inspection	Annually
• Corrosion Inspection	Annually
• Pull Test Certification	Annually
• Replacement If Damaged	Immediate

SAFETY INFORMATION

- Intended for fall prevention systems only.
- Not designed for lifting applications.
- Do not exceed system design loads.
- Use approved fall arrest PPE.
- Follow manufactured installation procedure.
- Remove from service immediately if damaged or deteriorated, or excessive corrosion is detected.

COMPATIBLE COMPONENTS

	8mm Stainless Steel Wire
	Carabiner Hooks
	Ropes
	Sling with Tensioner

